

# H5PNF-S

Type N Female with gas barrier for 7/8 in HJ5-50 air dielectric cable



## Product Classification

<b>Brand</b>	HELIAX®
<b>Product Type</b>	Air coaxial connector

## General Specifications

<b>Interface</b>	N Female
<b>Body Style</b>	Straight
<b>Brand</b>	HELIAX®
<b>Gas Barrier</b>	Yes
<b>Mounting Angle</b>	Straight

## Electrical Specifications

<b>Connector Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	0 – 5200 MHz
<b>Cable Impedance</b>	50 ohm
<b>RF Operating Voltage, maximum (vrms)</b>	707.00 V
<b>dc Test Voltage</b>	2 kV
<b>Insulation Resistance, minimum</b>	5000 MOhm
<b>Average Power</b>	0.6 kW @ 900 MHz
<b>Peak Power, maximum</b>	10.00 kW
<b>Insertion Loss, typical</b>	0.05 dB

## Mechanical Specifications

<b>Outer Contact Attachment Method</b>	Tab-flare
<b>Inner Contact Attachment Method</b>	Self-tapping
<b>Outer Contact Plating</b>	Silver
<b>Inner Contact Plating</b>	Silver

## Dimensions

<b>Nominal Size</b>	7/8 in
---------------------	--------

# H5PNF-S

---

<b>Diameter</b>	41.50 mm   1.63 in
<b>Length</b>	73.00 mm   2.87 in
<b>Weight</b>	0.35 kg   0.77 lb

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Storage Temperature</b>	-70 °C to +85 °C (-94 °F to +185 °F)
<b>Moisture Resistance Test Method</b>	MIL-STD-202, Method 106
<b>Mechanical Shock Test Method</b>	MIL-STD-202, Method 213, Test Condition I
<b>Thermal Shock Test Method</b>	MIL-STD-202, Method 107, Test Condition A-1, Low Temperature -55 °C
<b>Vibration Test Method</b>	MIL-STD-202, Method 204, Test Condition B
<b>Corrosion Test Method</b>	MIL-STD-202, Method 101, Test Condition B

## Return Loss/VSWR

<b>Frequency Band</b>	<b>VSWR</b>	<b>Return Loss (dB)</b>
0–1000 MHz	1.02	40.09
1–2200 MHz	1.03	36.61
2200–4000 MHz	1.08	28.3
4000–5200 MHz	1.15	23.13

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



## \* Footnotes

**Insertion Loss, typical** 0.05√freq (GHz) (not applicable for elliptical waveguide)