

NICKEL, SCREW TOGETHER HOODS, C CLIP

DTZK SERIES

TECHNICAL SPECIFICATIONS


Material:	Zinc, Nickel plated
Operating Temperature:	-40°C to +120°C
Cable Entry:	Top
Thumbscrews:	UNC 4-40 (standard)
	M2.5, M2.6 or M3.0 on request
Cable Diameter:	From 4.3 mm Up to 13.0 mm

FEATURES

- Available in sizes 9-15-25-37
- Excellent EMI Shielding
- Re-openable
- Strain relief inserts ensure a secure termination
- Full Metal Jackscrew as standard
- Plastic Cap Jackscrew on request

Size	Product Code
9-way	DTZK9-K
15-way	DTZK15-K
25-way	DTZK25-K
37-way	DTZK37-K

Size	Dim A	Dim B	Dim C
9-way	15,0	39,9	31,2
15-way	15,0	41,5	39,5
25-way	15,0	48,6	53,4
37-way	15,0	53,6	69,7



BLACK, SCREW TOGETHER HOODS, C CLIP

DTZK-BK SERIES

TECHNICAL SPECIFICATIONS

Material:	Zinc, Black
Operating Temperature:	-40°C to +120°C
Cable Entry:	Top
Thumbscrews:	UNC 4-40 (standard)
	M2.5, M2.6 or M3.0 on request
Cable Diameter:	From 4.3 mm Up to 13.0 mm

FEATURES

- Available in sizes 9-15-25-37
- Excellent EMI Shielding
- Re-openable
- Strain relief inserts ensure a secure termination
- Full Metal Jackscrew as standard
- Plastic Cap Jackscrew on request

Size	Product Code
9-way	DTZK9-BK-K
15-way	DTZK15-BK-K
25-way	DTZK25-BK-K
37-way	DTZK37-BK-K

Size	Dim A	Dim B	Dim C
9-way	31,2	39,9	15,0
15-way	39,5	41,5	15,0
25-way	53,4	48,6	15,0
37-way	69,7	53,6	15,0

