


# Product data sheet

IMS CONNECTOR SYSTEMS GmbH  
 Obere Hauptstrasse 30  
 D-79843 Löffingen  
 Postfach 1141  
 D-79840 Löffingen

Tel (+49) 7654 901-0  
 Fax (+49) 7654 901-199  
 Net: www.imscs.com  
 E-mail: sales@imscs.com

<b>Part Number: 53.2525.401</b>  <b>Description: p.c.b. mount angle jack</b>		Revision: - Date: <b>11.10.2007</b> Signature: <b>IS</b>  Page: 1 of 2	
<b>Design according to:</b>		<b>DIN 41626 Teil2 (Type HF5)</b>	
<b>Electrical characteristics:</b>		colored value means: still under test target value	
	Value	Unit	Picture
Impedance ( MIL-C- 39012B)	<b>50</b>	[ $\Omega$ ]	
Operating frequency up to	<b>4</b>	[GHz]	
Return loss measured with cable typ:	-	-	
1 GHz	<b>26</b>	[dB]	
2 GHz	<b>25</b>	[dB]	
4 GHz	<b>17</b>	[dB]	
6 GHz	-	[dB]	
10 GHz	-	[dB]	
18 GHz	-	[dB]	
3rd. Order PIM product 2x43dBm	/	[dBc]	
Insulation resistance	<b>1</b>	[G $\Omega$ ]	
Contact resistance			
Centre contact	<b>&lt; 10</b>	[m $\Omega$ ]	
Outer contact	<b>&lt; 3</b>	[m $\Omega$ ]	
Contact current max. (DC)	<b>1,5</b>	[A]	
Operating voltage	<b>250</b>	[V]	
Proof voltage	<b>750</b>	[V]	
<b>Mechanical characteristics:</b>		Value	Unit
Engagement force	<b>max. 10</b>	[N]	Remarks
Separating force	<b>min. 1</b>	[N]	
Mating cycles	<b>&gt; 500</b>		

# Product data sheet

IMS CONNECTOR SYSTEMS GmbH  
 Obere Hauptstrasse 30  
 D-79843 Löffingen  
 Postfach 1141  
 D-79840 Löffingen

Tel (+49) 7654 901-0  
 Fax (+49) 7654 901-199  
 Net: www.imscs.com  
 E-mail: sales@imscs.com

<b>Part Number:</b> 53.2525.401	Revision: -
<b>Description:</b> p.c.b. mount angle jack	Date: 11.10.2007
	Signature: IS
	Page: 2 of 2

Material & plating:	RoHS (2002/95/EC) conform	
	Material	Plating
Outer contact	<b>Brass</b>	<b>Cu + Ni + 0,8µm Au</b>
Centre contact	<b>Copper beryllium</b>	<b>Cu + Ni + 1,3µm Au</b>
Crimp ferrule	-	-
Other metal parts	<b>Bronze</b>	<b>Cu + 3-5µm Ni</b>
Insulator	<b>PTFE</b>	-
Gasket	-	-

Environmental influences:		Remarks
Operating temperature range	-55°C up to +125°C	
	Standard	
Climatic sequence:	IEC 60068-2-61	
1. Dry heat	IEC 60068-2-2-Ba	
2. Damp heat, cyclic, 1 cycle	IEC 60068-2-30-Db	
3. Cold	IEC 60068-2-1-Aa	
4. Damp heat, cyclic, 6 cycles	IEC 60068-2-30-Db	
Solder profile:	-	

**Notes:**

Update historie			
Rev.	Date	Alteration	Signature

Formblatt-Nr.: Form-TK-012b	
Rev.	01
Released	17. Aug 07