



# Product data sheet

IMS CONNECTOR SYSTEMS GmbH  
 Obere Hauptstrasse 30  
 D-79843 Löffingen  
 Postfach 1141  
 D-79840 Löffingen

Tel (+49) 7654 901-0  
 Fax (+49) 7654 901-199  
 Net: www.imscs.com  
 E-mail: sales@imscs.com

<b>Part Number:</b> 3367.01.1420.026	<b>Revision:</b> h
<b>Description:</b> Cable mount angle plug	<b>Date:</b> 16.08.2005
	<b>Signature:</b> U. Mayer
	<b>Page:</b> 2 of 2

<u>Material &amp; plating</u>	Material	Plating
Housing	stainless steel	-
Centre contact	brass	Cu + Ni + 1,3µm Au
Cap	brass	Cu + 2-4µm CuZnSn
Insulator	SPS	-
Crimp ferrule	copper	Cu + 2-4µm CuZnSn
	-	-

<u>Environmental influences</u>		Remarks
Operating temperature range	-40°C up to +125°C Standard	
Climatic sequence: 1. Dry heat 2. Damp heat, cyclic, 1 cycle 3. Cold 4. Damp heat, cyclic, 6 cycles	IEC 60068-2-61 IEC 60068-2-2-Ba IEC 60068-2-30-Db IEC 60068-2-1-Aa IEC 60068-2-30-Db	

**Notes & Remarks**

1.) Mating and separation force checked, in not inserted status (housing only), with gauge (IMS-No) 9/449-1.

2.) Plug-in system with counterpart in brass: recommended <50 cycles.

<u>Update historie</u>		
Rev.	date	Signature
g.	16.08.2005	uma
h	19.06.2008	uma